

ACCEPTED VENDORS:
ALLIED ELECTRONICS
7151 JACK NEWELL BLVD. S.
FORT WORTH, TX 76118
866-433-5722

NEWARK ELEMENT 14
33190 COLLECTION CENTER DRIVE
CHICAGO, IL 60693-0331
800-463-9275

DIGI-KEY ELECTRONICS
701 BROOKS AVENUE SOUTH
PO BOX 677
THIEF RIVER FALLS MN 56701-0677
800-344-4539



MANUFACTURER:
TE CONNECTIVITY

RATED VOLTAGE: 24VDC
LIMITING CONTINUOUS CURRENT: 45A AT NORMALLY CLOSED 23°C, 30A AT 85°C
RATED COIL POWER: 2.1W
OPERATING TEMP: -40C TO 125C
DEGREE OF PROTECTION, IEC 60529: IP54 (DUSTPROOF), IP67 (SEALED)
TERMINAL TYPE: QUICK DISCONNECT
FLAMMABILITY: UL94-HB


REVISION HISTORY					
REV	DATE	DESCRIPTION	AUTHOR	CHECKED BY	APPROVED
A	9/5/17	INITIAL RELEASE	JT	LS	JT
B	10/31/18	ADDED REV BLOCK; ADDED FLAMMABILITY RATING; ADDED TEMPERATURE CONSTRAINTS TO LIMITING CONTINUOUS CURRENT; FIXED -1 MANUFACTURER PART NO. WAS V23134A10056X432 NOW V23134A0056X432; ADDED SHT 2 W/ -3 PART.	ZA	LS	CR

PART NO.	MANUFACTURER PART NO.	DIODE	ALLIED ELECTRONICS P/N	NEWARK ELEMENT 14 P/N	DIGI-KEY ELECTRONICS P/N	MOUSER ELECTRONICS P/N	VELVAC P/N
ES50186-1	1-1414167-0 (V23134A0056X432)	YES	N/A	94T6087	1-1414167-0-ND	655-1-1414167-0	N/A
ES50186-2	6-1393302-3 (V23134A1053C643)	NO	70289065	31M6174	A122268-ND	655-V23134A1053C643	N/A
ES50186-3	091236	NO	N/A	N/A	N/A	N/A	091236



MOUSER ELECTRONICS
1000 NORTH MAIN ST
MANSFIELD, TX 76063
800-346-6873



ES50186-1
COD
1 form C, 1 CO
with diode



ES50186-2 & -3
1 form C, 1 CO



TERMINAL DESCRIPTION	
TERMINAL NO.	FUNCTION
30	LOAD IN
85	COIL
86	COIL
87	CONTACT NO
87a	CONTACT NC

NOTE:

This drawing defines the overall geometry and performance specifications of the part/assembly, and constitutes the acceptance criteria thereof. Only the item(s) described in this document procured from the vendor and/or manufacturer listed hereon are approved for use. A substitute item shall not be used without prior approval. Conformance of hardware to these requirements is acceptable in lieu of vendor and/or manufacturer documentation.

~CONFIDENTIAL INFORMATION~
THE INFORMATION AND DATA CONTAINED HEREIN IS PROPRIETARY AND IS SUBMITTED IN CONFIDENCE, AND SHALL NOT BE DISCLOSED, USED OR DUPLICATED FOR ANY PURPOSE WHATSOEVER WITHOUT THE PRIOR WRITTEN PERMISSION OF PARAVION TECHNOLOGY, INC.

PROTO


Paravion® Technology Inc.		TITLE		DRAWING NUMBER	
RELAY, 40AMP		ES50186			
DIMENSIONS IN INCHES TOLERANCES EXCEPT WHERE NOTED: X = ±.1 .XX = ±.05 XXX = ±.010 ANGLES = ± 1°		DRAWN BY	CHK'D BY	APPRO'D BY	DATE
THREADS INTERNAL CLASS 2B EXTERNAL CLASS 2A		JT	LS	JT	9/6/17
3RD ANGLE PROJECTION		DO NOT SCALE DRAWING		REV	ECO
		©2018 PARAVION TECH INC. PARAVION IS A TRADEMARK OF PARAVION TECHNOLOGY INC.		B	
		SHEET		1 OF 2	

NOTES:



- 1. THIS DRAWING DEFINES THE OVERALL GEOMETRY AND PERFORMANCE SPECIFICATION OF THE PART/ASSEMBLY, AND CONSTITUTES THE ACCEPTANCE CRITERIA THEREOF. CONFORMANC OF HARDWARE TO THESE REQUIREMENTS IS ACCEPTABLE IN LIEU OF VENDOR DOCUMENTATION.
- 2. ACCEPTED MFR'R: VELVAC.
- 3. SEE DATA SHEET FOR DETAILED INFORMATION.

-3 RELAY

DASH NO.	MFR P/N	DESCRIPTION	VOLTS COIL	WATTS COIL	VOLTS CONTACT	AMPS CONTACT	WEIGHT (OZ)
-3	091236	RELAY	24	1.6	24	20	1.3



TERMINAL DESCRIPTION	
TERMINAL NO.	FUNCTION
30	LOAD IN
85	COIL
86	COIL
87	CONTACT NO
87a	CONTACT NC



Paravion® Inc.		TITLE		DRAWING NUMBER	
RELAY, 40AMP		ES50186			
DIMENSIONS IN INCHES TOLERANCES EXCEPT WHERE NOTED X = ±.1 .XX = ±.05 .XXX = ±.010 ANGLES = ± 1°		DRAWN BY	CHK'D BY	APP'D BY	DATE
		JT	LS	JT	9/6/17
THREADS INTERNAL: CLASS 2B EXTERNAL: CLASS 2A		DO NOT SCALE DRAWING		REV	ECO
3RD ANGLE PROJECTION		© 2018 PARAVION TECH INC. PARAVION IS A TRADEMARK OF PARAVION TECHNOLOGY INC.		B	
		SHEET		2 OF 2	

—CONFIDENTIAL INFORMATION—
THE INFORMATION AND DATA CONTAINED HEREIN IS PROPRIETARY AND IS SUBMITTED IN CONFIDENCE, AND SHALL NOT BE DISCLOSED, USED OR DUPLICATED FOR ANY PURPOSE WHATSOEVER WITHOUT THE PRIOR WRITTEN PERMISSION OF PARAVION TECHNOLOGY INC.

PROTO